South Korean Made Diecutters. Globally Acclaimed Performance.

YoungShin

1



QUEST-270

## QUEST-270 Flatbed Diecutter for Digital Print Output

**MAKING SHORT-ORDER OF DIECUTTING SHORT ORDERS** 

### DIECUTS UP TO 10 SHEETS PER MINUTE

- + Designed for chipboard and corrugated digital printers
- + Job make-ready in less than 15 minutes
- + Replaces time-consuming plotter process
- + Small footprint easily placed near digital printer
- + Can optionally run substrates up to 76.2mm

Maximum Sheet Size 2,700mm x 1,700mm

Minimum Sheet Size 650.2mm x 450mm

Maximum Cutting Size 2,700mm x 1,709.9mm

Maximum Sheet Thickness .99mm up to optionally 76.2mm Maximum Speed 300 SPH

II

**Die-Cutting Pressure** 500 tons

**Moving Table** Type = Stroke: Knuckle

### QUEST-27() Flatbed Diecutter for Digital Print Output

### utter for Output

# YoungShin



#### **Feeding Section**

Flatbed technology increases productivity by 10%–15% since a new sheet can be placed onto the platen while removing the completed die cut sheet. Includes both feeding and delivery tables.



#### **Chase and Tool Changeover**

Operator is stationed at the front directly above the cutting plate since the chase frame is easily removed for easy and highlyaccurate operation increasing speed and turnaround time.



#### **Die Cutting Section**

Sophisticated electronics control pressure settings at the front of the unit providing easy adjustments and precise alignment on the substrate's four corners.



#### **Speed and Control**

Four (4) operating modes of the cutting plate include single cycle, continuous cycle, dwell, and variable speed control allow die cutting of thin vinyls and PVCs.



#### **Remote Diagnostics**

Touch screen remote diagnostics (eWon System) are integrated with safety and aerial sensors on the cutting plate. UL labeled sensors and motors are included.



#### **Expanded Substrates**

Option available to die cut up to 76.2mm substrates including triple wall corrugated.



#### Maintenance

Mechanics are in a self-contained area providing automatic lubrication of moving components while well-positioned indicator panels and dials provide rapid and streamlined operations.



#### Safety

Incorporates integrated laser and light curtain safeguards to prevent improper or unsafe operations combining both safety and productivity.



#### **Additional Option**

An optional heated bed that prevents "bruising" for clear plastic substrates is available that prolongs the tool.

## FOR MORE INFORMATION

www.diecutter.co.kr

Sales Department Young Shin Industries, Ltd. 629 Daecheon-Dong, Dalseo-Gu Daegu, Korea (Zip Code 42718) P: +82 53 582 8800 F: +82 53 582 6928 E-Mail: diecutter@diecutter.co.kr