

REVOTE 1040S

AUTOMATIC FLATBED DIECUTTER



www.diecutter.co.kr

Revolutionary
Diecutting Technology
For the Future

YoungShin

**South Korean Made Diecutter.
Globally Acclaimed Performance.**




Specifications of REVOTEC 1040S

Maximum Sheet Size	1040 × 740 mm	40.94" × 29.13"
Minimum Sheet Size	440 × 340 mm	17.32" × 13.38"
Maximum Cutting Size	1040 × 730 mm	40.94" × 28.74"
Inside Chase	1100 × 764 mm	43.30" × 30.07"
Minimum Gripper Margin	8 mm	0.31"
Cutting Pressure	300 tons	330 US tons
Sheet Thickness	Carton Board 0.1 ~ 1.5 mm Corrugated Board (E,B Flute) : 4 mm	Carton Board 0.004" ~ 0.060" Corrugated Board (E,B Flute) : 0.157"
Maximum Speed	7500 s/h	7500 s/h
Required Power Supply	22 Kw	22 Kw
Main Motor	11 Kw	11 Kw
Weight	17 tons	17 US tons




FEEDER

With Suction Device in mechanical driving, sheets smoothly fed.



FEEDING CONVEYOR

Makes the feeding of thin sheets and warped sheets a possibility.



SIDE LAY

Side Lay with sensor ensures excellent register by proximating the distance between side and front lay more.



GRIPPER

Enhanced durability for the Gripper Bar and Drive.




CHASE

Chase turn-over and center line ensure quick order change.




TOUCH SCREEN

Clear and simple readings ensures quick fault finding and machine operation. Cutting pressure gauge ensures machine and cutting die durability by checking cutting pressure and over-cutting pressure.



STRIPPING SECTION

Waste stripping with Upper and Lower pins.



DELIVERY SECTION

Automatic counter and tabbing inserter ensure reliability and productivity, and batching.